

## V9-SPC-IP-HK2A



### Features:

1080P HD resolution, clear and fine images run with Single Power Cable, Single Phase ;  
 Support 2D/3D noise reduction, digital wide dynamic;  
 Advanced H.265/H.264 video compression, Super low rate, high definition quality of image;  
 Professional antilightning, conform to GB/T17626.5 and IEC61000-4-5.  
 Support ONVIF; access third party  
 Support various mobile monitoring (iPhone, Android);  
 Provide web CMS, center platform management software MYEYE, provide SDK development  
 Support cloud technology, easy to achieve network penetration, from in-line and alarm information pushed

### Parameters :

System structure	Embedded RTOS, dual-core 32bit DSP pure hard compression, watch dog
Sensor	2.0M CMOS sensor, color 0.1Lux@F1.2, black/white 0.01Lux@F1.2
Video compression	H.265/H.264, support dual stream, AVI; 0.1M~8Mbps variable; 1~30f/s variable
Shutter	1/50(1/60)s to 1/10,000s
Lens	2.8/3.6/6mm( Optional)
Day and night	Support IR-CUT
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Audio compression	G.711, support bidirectional talk, audio&video synchronization
Audio interface	1ch input, level: 2Vp-p, impedance: 1kΩ, support sound pick-up input; 1ch output, impedance: 16Ω, 30mw, support microphone (O)
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc
Signal interface	One photo resistance interface, one IR-CUT interface, support photo resistance signal and IR-CUT links to IR
Alarm I/O	1/0 (support alarm input and video link to background)
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Other function	Support WEB, OSD, live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture; united remote client monitoring software MYEYE; perfect SDK;
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Power	DC12V
IR Range	Upto 20 Mtrs.
Other	Support POE power supply (optional), not support any custom